

GUARDIAN CONCRETE SWIVEL ANCHOR

Guardian Fall Protection 26609 79th Ave S Kent WA 98032 phone: (800) 466.6385 fax: (800) 670.7892 www.guardianfall.com

Part #	Description
00242	Swivel Concrete Anchor Kit Includes 00241: Swivel Concrete Anchor Bolt HSL-3-B M12/5
00243	Swivel Concrete Anchor Bolt (5 Pack) - HSL-3-B M12/5
00244	Swivel Concrete Anchor Bolt (12 Pack) - HSL-3-B M12/5

SPECIFICATIONS

- Weight: 1.2 lbs
- Dimensions: 5.73" (L) x 3" (W) x 4 1/2" (H)
- Weight capacity: 310 lbs
- Minimum breaking strength: 5,000lbs
- Minimum compression strength: 3,000 psi
- Hole size for installation: 11/16", 18mm or a 3/4" hole (No special drill bits are needed)
- The D-ring bracket is made of zinc plated steel
- The D-ring is made of forged alloy steel
- Meets all applicable OSHA and ANSI standards
- Visual indicator that allows the user to see that the anchor is hooked up properly, Red to Green

INSTALLATION

- The drilled hole must be at least 15" from any free edge
- Thickness of concrete must be at least 6 1/4"
- Minimum spacing is 10" for multiple anchor installation
- Tighten the bolt to 59 ft lbs using a 15/16" torque wrench
- Can be used with a GFP Lanyard, Self Retracting Lifeline, or HLL System



1 SAFETY

This secure anchor point is rated at 5,000 lbs, swivels 360° degrees and meets or exceeds OSHA and ANSI standards.



2 APPLICATIONS

Perfectly suited for temporary or permanent applications. The Re-Usable D-Ring Assembly only requires you to install a new bolt.



3 STURDY DESIGN

Sturdy design of high strength plated steel and stainless steel makes the anchor capable of working in a wide variety of punishing environments.

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR