

RENTAL

anchor points

NEW

EcoAnchor

Part#	Description
30801	EcoAnchor



- Material: Fire resistant neoprene
- Surface Contact Dimensions: 4'4" x 4'4"
- Weighs: Empty = 17 lb., Full = 947 lb.
- Pressure Loading: 50 lb. per square foot
- Puncture resistant
- Patent Pending No.0901634.6

In direct partnership with CHECKMATE, an industry leading fall protection manufacturer in the UK, Guardian is excited to introduce the EcoAnchor. As a stocking supplier of the EcoAnchor, a distributor can expect quick turnaround to meet your customer and production needs.

The EcoAnchor, which is available for rent, offers end users an alternative to the heavy-to-transport system like our Angel Anchor. The EcoAnchor has the following features and benefits.

- Water filled neoprene counterweight fall arrest anchor system
- Sold individually as a single point fall arrest anchor or in a kit with Guardian's 4-Person 80' Temporary Horizontal Lifeline Fall Arrest Anchor System (page 139)
- Tested & approved for use on a wide variety of low slope roof surfaces
- Weighs less than 17 lb. when empty & comes with a carry bag for stowing
- Requires no holes to be drilled in mounting surface
- Requires no heavy weights be lifted to mounting surface
- Installs faster (fills in 8 to 10 minutes) than traditional counterweight systems
- Less expensive than traditional rooftop counterweight systems